

Better Pack[®] 755eS/755eM

ELECTRIC WATER-ACTIVATED TAPE DISPENSERS



Versatile, Rugged and Reliable

The Better Pack 755eS and 755eM excel in demanding, fast-paced environments, especially when sealing random-sized cartons. The 755eS is engineered for 115V and the 755eM is engineered for 220V. Twenty preset buttons provide exceptional operational flexibility with one touch, quickly handling different box sizes. Since the dispensers accommodate tape that is up to 4 inches wide (10.2 cm), they are particularly good for applications requiring extra reinforcement, such as when shipping large or heavy items.

Easy to Operate

- Smooth touch, color-coded key pad with 20 pre-set tape lengths
- Random key allows for continuous, uninterrupted tape dispensing
- Side opening cover provides easy tape loading access

Safe, Convenient and Dependable

- UL Listed and Approved; built to meet or exceed safety standards set by CE (Europe) and CSA (Canada); RoHS compliant*
- Low profile design provides pack station placement flexibility
- Heavy gauge steel frame construction and few moving parts means minimal maintenance
- Low voltage adjustable water heater warms the water, optimizing tape bonding
- Exposed, large 64 oz. (1.9 liters) water bottle provides water level visibility and easy refill

Model #	Electrical Requirements	Preset Tape Length Range	Tape Width	Gum In or Gum Out (Tape)
755eS	115v	6" to 75" plus up to 120" random lengths	1" - 4"	Gum In or Gum Out
755eM	220v	15.24 cm to 190.5 cm plus up to 305 cm random lengths	2.5 cm to 10.2 cm	Gum In or Gum Out

* Certificate Copies Available Upon Request

BETTER PACKAGING SYSTEMS, INC
P: 800-722-8002: E: TAPESHOOT@AOL.COM

**BETTER
 PACKAGES[®], Inc.**
A WHOLLY OWNED SUBSIDIARY OF 

Better Pack® 755eS/755eM



	Model	Specifications
Dimensions	755eS	21" L x 10.5" W x 9.5" H
	755eM	53.3 cm x 26.7 cm x 24.1 cm
Shipping Weight	755eS	42 lbs.
	755eM	19.05 kg
Maximum Roll Size	755eS	Up to 600' roll of tape; Up to 7.5" diameter
	755eM	Up to 182.9 m roll of tape; Up to 19.05 cm diameter
Tape Width	755eS	1" to 4"
	755eM	2.54 cm to 10.16 cm
Dispensing Speed	755eS	32"/second
	755eM	81 cm/second
Water Bottle Capacity	755eS	64 ounces
	755eM	1.9 liters
Electrical Requirements	755eS	115V, 60 Hz, 4 Amps
	755eM	220V, 50 Hz, 2 Amps
Safety Compliance	755eS 755eM	UL Listed, meets CE and CSA standards; RoHS compliant
Warranty	755eS	2 years parts and materials,
	755eM	6 months labor



8323 MARTINGALE LANE
 NOVELTY, OHIO 44072
 Toll Free in US: 80-722-8002
 P: (440) 338-7044
 F: (440) 338-7046
 E: TAPESHOOT@AOL.COM